


CUSTOMER DATASHEET


Printed: 05/06/2018


Product Management
Transportation Europe

Central Article Code: LB1028G19-A Created: 06/09/2005

Local Code: Modified: 03/05/2018







Final Outlook LB119-A Approval date 15/08/2011

| PERFORMANCES | | | CONTAINER | | | |
|---|---------|------|-----------------------------|---------------------------------|---------|--|
| Voltage (V): | 12 V | | Type: | LB1 | BLACK | |
| C20 (Ah): | 40.0 | 20 h | Hold Down: | B4 | | |
| Cranking (A): | 280 | EN | H.D. Adapter: | No | | |
| Charge: | CHARGED | | COVER | | | |
| Technology: | GEL | | Type: | DIN | BLACK | |
| Grid: | Ca/Ca | | Polarity: | ETN 0 | | |
| | | | Terminals: EN full Ford lug | | ord lug | |
| | | | Terminal Adapter: | No | | |
| | | | SOCI: | No | | |
| | | | Ventilation: | Ventilation: Independent | | |
| | | | Filter: | No | | |
| | | | Lateral Plug: | No | | |
| STD. DIMENSIONS | | | PLUGS | | | |
| Length (mm ± 2): | 207 | | Type: 6 x M18 Va | Type: 6 x M18 Valve GREY MEDIUM | | |
| Width (mm ± 2): | 175 | | HANDLES | | | |
| Height (mm ± 2): | 175 | | | | | |
| | | | Type: None | | | |
| | | | OTHERS | | | |
| | | | Degassing Tube: | No | | |
| All figures show nominal EN50342 and applicable | | | | | | |