


CUSTOMER DATASHEET


Printed: 04/02/2022


Product Management Transportation Europe

D07076G02-A Created: 06/09/2005 Central Article Code:

ES1200 Modified: 20/03/2019 Local Code:







Final Outlook D0702-A Approval date 01/10/2005

PERFORMANCES

Voltage (V): 12 V

C20 (Ah): 110.0 20 h ΕN Cranking (A):

Charge: **CHARGED**

Technology: **GEL** Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: 200 cycles@100%

CONTAINER

D07 **BLACK** Type: Hold Down: B0 No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 2

H.D. Adapter:

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 286 Width $(mm \pm 2)$: 269 Height (mm ± 2): 230 Total Weight (kg ± 5%): 37.50

PLUGS

6 x M18 Valve **GREY MEDIUM** Type:

HANDLES

2 x Rope (Rigid holder) BLACK Type:

OTHERS

Degassing Tube: No

Gel

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.