



TECHNICAL DATASHEET


Printed: 13/06/2013 Product Management

Transportation Europe

Central Article Code: D06103G09-A Created: 06/09/2005 ETN Code or Other: ES2400 Modified: 5/26/2011







Final Outlook D0609-A
Approval date 01/11/2010

PERFORMANCES		
Voltage (V):	12 V	
C20 (Ah):	210.0	20 h
Rc (min):	0	
Cranking (A):	1030	EN
Vibration:	V3 (35Hz/6g/20h)	
Endurance:	250 cycles@100%	
Charge:	CHARGED	
Technology:	GEL	

Ca/Ca

Type: D06 BLACK
Hold Down: B0
H.D. Adapter: No

COVER

CONTAINER

Type: Flat/Screw BLACK

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

WEIGHT AND STD. DIMENSIONS

 Battery Weight (kg):
 67.00

 Volume acid (l):
 0.00

 Length (mm):
 518

 Width (mm):
 279

 Height (mm):
 240

Grid:

Type: 6 x M18 Valve GREY MEDIUM

HANDLES

Type: 2 x Rope (Rigid BLACK

OTHERS

PLUGS

Degassing Tube: No

Gel

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.