

ODS-AGM16CL (PC625)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V	
Capacity (20-hour rate)	18Ah	
Capacity (10-hour rate)	17Ah	
Cold Cranking Amps (CCA, SAE J537)) 220A	
PHCA - 5-second pulse current	540A	
HCA	400A	
MCA	330A	
Reserve capacity	26 mins	
Short circuit current (using IEC method)	1800A	
Internal resistance at 20 $^{\circ}\text{C}$ (using IEC	method) $7~m\Omega$	

Dimensions & Weight

Length	170 mm
Width	99 mm
Height (to top of terminals)	178 mm
Height Container	175 mm
Weight	6 kg

Temperature

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.


Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%


Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

Terminal Type M6 FEMALE THREAD THREAD



ODS-AGM16CL RIGHT POSITIVE FRONT FEMALE CONNECTION



PDF Generated at https://eu.odysseybattery.com 08/03/2022 12:55:18 Information correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780