

# ODS-AGM16LMJ (PC680MJ)

# Technical Data Sheet

# **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

## **Power & Performance**

Voltage		12V
Capacity (20-hour rate)		16Ah
Capacity (10-hour rate)		16Ah
Cold Cranking Amps (CCA,	SAE J537)	170A
PHCA - 5-second pulse cur	rent	520A
HCA		350A
MCA		280A
Reserve capacity		24 mins
Short circuit current (using	IEC method)	1800A
Internal resistance at 20°C	(using IEC method)	$7~\text{m}\Omega$

# **Dimensions & Weight**

Length	185 mm
Width	79 mm
Height (to top of terminals)	163 mm
Height Container	170 mm
Weight	7.5 kg

# **Temperature**

Operating Temperature Range	-40°C to +80°C
Optimum Storage Temperature	+20°C

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

# Charging & self-discharge

Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

# Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 08/03/2022 12:52:31 Information correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627

EH Europe GmbH Baarerstrasse 18 6300Zug.

EnerSys Asia Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780

# EnerSys

# **Terminal Position**



