

ODX-AGM31 (31-PC2150S)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V
Capacity (20-hour rate)	100Ah
Capacity (10-hour rate)	92Ah
Cold Cranking Amps (CCA, SAE J537)	1150A
PHCA - 5-second pulse current	2150A
HCA	1545A
MCA	1370A
Reserve capacity	205 mins
Short circuit current (using IEC method)	5000A
Internal resistance at 20°C (using IEC method)	$2.2~\text{m}\Omega$

Dimensions & Weight

Length	330 mm
Width	173 mm
Height (to top of terminals)	241 mm
Height Container	216 mm
Weight	35.3 kg

Temperature

Operating Temperature Range	-40°C to +80°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%


Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).


Extreme
AGM² OD VSS EY


Extreme
AGM² OD AGM91

Terminal Position



Terminal Type





PDF Generated at https://eu.odysseybattery.com 08/03/2022 12:25:14 Information correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780