



# HR12-150W(12V150W)

## Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	150W@15min-rate to 1.67V per cell @25°C
Weight	Approx. 12.4 Kg (Tolerance ±3.0%)
Internal Resistance	Approx. 8.5 mΩ
Terminal	F11(M6)
Max. Discharge Current	400A (5 sec)
Short Circuit Current	1100A
Design Life	15 years
Max. Charging Current	12.0 A
Reference Capacity	C10 37.8AH C20 40.0AH
Standby Use Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Equalization Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



HR ( High Rate ) series Valve Regulated Lead Acid (VRLA) battery is designed for heavy load discharge applications with 15 years design life in float service. By using strong grids, thick plate and specially designed active material. It is with lower I.R, lower self discharge rate, high power, and longer service life. The HR series battery offers 30% more power output than the standard series. It is suitable for high power standby used, such as datacenter, UPS, EPS etc.



ISO 9001



ISO 14001







OHSAS 18001



MH 28539



## Dimensions



F11 TERMINAL

Length	198±2mm (7.80 inches)
Width	166±2mm (6.54 inches)
Height	169±2mm (6.65 inches)
Total Height	169±2mm (6.65 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

### Constant Current Discharge Characteristics : A (25°C)

F.V/Time	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
1.60V	149.9	124.1	108.7	83.0	67.5	49.8	28.8	20.7
1.67V	136.0	113.8	100.5	77.4	63.5	47.1	27.5	19.8
1.70V	130.2	109.4	96.9	75.0	61.7	46.0	26.9	19.5
1.75V	120.2	101.9	90.8	71.0	58.6	44.0	26.0	18.8
1.80V	110.2	94.4	84.8	67.1	55.9	42.2	25.1	18.2
1.85V	94.6	80.4	71.8	57.7	48.5	37.3	22.6	16.6

### Constant Power Discharge Characteristics : WPC (25°C)

F.V/Time	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
1.60V	275.4	231.1	204.5	158.1	129.8	96.7	54.1	39.1
1.67V	256.4	216.8	193.0	150.0	123.9	92.8	52.1	37.8
1.70V	247.9	210.3	187.6	146.5	121.2	90.9	51.2	37.3
1.75V	232.7	198.7	178.2	140.2	116.4	87.9	49.8	36.3
1.80V	216.5	186.5	168.3	134.0	112.0	84.8	48.3	35.3
1.85V	188.6	161.1	144.5	116.4	98.1	75.7	44.0	32.5

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.

# HR12-150W(12V150W)



Supplementary charge required  
(Carry out supplementary charge)

## Temperature Effects On Capacity

## Effect Of Temperature On Long Term Life